

00006412

MATERIAL SAFETY DATA SHEET

Page 1

K-G SPRAY-PAK INC.
 8001 KEELE STREET, P.O BOX 89
 CONCORD; L4K 1Y8; ONTARIO
 CANADA 905-669-9855

PRODUCT: 1808-10-132 TIRE SHINE 450G



Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER K-G SPRAY-PAK INC.
 8001 KEELE STREET P.O. BOX 89
 ONTARIO
 CANADA
 L4K 1Y8
 CANUTEC EMERGENCY #:1-613-996-6666(24HR)
 PRODUCT NAME..... 1808-10-132 TIRE SHINE 450G
 CHEMICAL FAMILY..... SILICONE LUBRICANT.
 MOLECULAR WEIGHT..... NOT APPLICABLE.
 CHEMICAL FORMULA..... MIXTURE.
 TRADE NAMES & SYNONYMS..... 1808-10-132 TIRE SHINE 450G
 PRODUCT USES..... CLEANER.
 FORMULA/LAB BOOK #..... F 10-009.

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
OCTYLPHENOL ETHOXYLATE	1-5	N/E	68987-90-6	N/E	N/E
ISOBUTANE	3-7	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	0.5-1.5	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
 INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.
 INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.
 EYE CONTACT..... MAY CAUSE IRRITATION.
 SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.
 SKIN CONTACT..... MAY CAUSE IRRITATION.
 EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.
 EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS
 EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... NOT AVAILABLE.
 SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.
 FLAMMABILITY..... NOT A FLAMMABLE PRODUCT (AS PER CANADIAN AEROSOL REGULATIONS).
 IF YES, UNDER WHICH CONDITIONS?.... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
 EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
 UPPER FLAMMABLE LIMIT..... 9.6.
 (% BY VOLUME)
 LOWER FLAMMABLE LIMIT..... 2.6.
 (% BY VOLUME)
 EXPLOSION DATA
 SENSITIVITY TO STATIC DISCHARGE. NOT APPLICABLE.

00006412

MATERIAL SAFETY DATA SHEET

Page 2

PRODUCT: 1808-10-132 TIRE SHINE 450G

Section 05: FIRE FIGHTING MEASURES

SENSITIVITY TO IMPACT..... NOT APPLICABLE.
 HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
 AEROSOL FLAME PROJECTION CLASSIFIED AS:..... 0 cm.
 FLASHBACK..... NONE.
 FLASH POINT(°C),TAG CLOSED-CUP -40F BASED ON PROPANE/ISOBUTANE.
 (CONCENTRATE)

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
 HANDLING PROCEDURES AND EQUIPMENT STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... NOT NORMALLY REQUIRED.
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
 EYE/TYPE..... SAFETY GLASSES.
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
 OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... MILKY WHITE.
 ODOR..... HYDROCARBON.
 ODOR THRESHOLD..... NOT AVAILABLE.
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 45-60.
 @ 20 C
 BOILING POINT (°C)(CONC)..... 92-100.
 EVAPORATION RATE..... GREATER THAN 1.
 n-BUTYL ACETATE = 1
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
 (BY WEIGHT)
 SOLUBILITY IN WATER g/L (20°C)..... SOLUBLE.
 pH..... 8-9.
 SPECIFIC GRAVITY (LIQUID)..... 0.98-1.0.
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
 FREEZING POINT: (°C)..... LESS THAN 0.
 AEROSOL PERCENT VOLATILE..... 85-86.
 (BY WEIGHT).
 SPECIFIC GRAVITY (AEROSOL)..... 0.84-0.88.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
 CHEMICAL STABILITY:
 YES..... UNDER NORMAL CONDITIONS.
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.
 COMPATIBILITY WITH OTHER SUBSTANCES:
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

00006412

MATERIAL SAFETY DATA SHEET

Page 3

PRODUCT: 1808-10-132 TIRE SHINE 450G

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... NO INFORMATION IS AVAILABLE AND NO ADVERSE REPRODUCTIVE EFFECTS ARE ANTICIPATED.

IRRITANCY OF MATERIAL..... MAY CAUSE IRRITATION.

SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.

CARCINOGENICITY OF MATERIAL..... THE INGREDIENTS OF THIS PRODUCT ARE NOT LISTED AS CARCINOGENS BY NTP, (NATIONAL TOXICOLOGY PROGRAM), NOT REGULATED AS CARCINOGENS BY OSHA, (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION), AND HAVE NOT BEEN EVALUATED BY IARC, (INTERNATIONAL AGENCY FOR RESEARCH ON CANCER), NOR BY ACGIH (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS).

TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.

MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).

Section 15: REGULATORY INFORMATION

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,D2B.

CNFC SECTION 3.3.5..... LEVEL 1.

CEPA (Canadian Environmental Protection ... Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.

HMIS RATING FLAMMABILITY..... 3 SERIOUS HAZARD.

HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.

HMIS RATING PERSONAL PROTECTION.. B.

NFPA CODE 30B..... LEVEL 1.

SARA 313 INFORMATION:..... THIS PRODUCT CONTAINS NO INGREDIENTS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372.

CAS #: . CHEMICAL

CALIFORNIA PROPOSITION 65:..... NAME: . N/A.

THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986: . WARNING: THIS PRODUCT DOES NOT INTENTIONALLY CONTAIN ANY CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CAS #: .

CHEMICAL NAME: . N/A.

TSCA (Toxic Substances Control Act) VOC (w/w%)..... 6-8.

Section 16: OTHER INFORMATION

NOTICE FROM K-G SPRAY- PAK INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY K-G SPRAY PAK INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. K-G SPRAY PAK INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... Regulatory Affairs

PREPARATION DATE May23/13