REV Brake Fluid Dot3

05-063 05-064

05-065

05-066 05-067 R529...

MATERIAL SAFETY DATA SHEET

SECTION1: MATERIAL DENT	FLAMMABLIIITY HEALTH	REACTIBITY PERSONAL PROCTION		
Material				
Name Identifier :	Brake Fluid Dot3			
Manufacturer's Name:	QUALITY LIQUID PA			
Address:				
	50 Tiffield Road Un	it 9		
City:		Province:		
Toronto		Ontario		
Postal Code:		Emergency Telephone#		
M1V 5B7		(416) 609-0828		
Trade Name & Synonyms			Material Use	
		R 529,		
Rev Brake Fluid Dot3		R530,R531,R532,R533,&R535		

Hazardous	Approximate	C.A.S.N.A or U.N	Hazard	LD50 LC50
Ingredients	Concentration %	Numbers		
Diethylene glycol	1-4%	111-77-3	combustible, toxic	Rat
monornethyl ether				LD50=4m/kg,LD50=9210mg/kg
				Rabbit:LD50µ1/kg
Triethylene glycol	<=40%	112-35-6	WHMIS, not hazardous.	Rat LD50=11300μ1/kg
monornethyl ether				Rabbit :LD50µ 1/kg
Triethylene glycol	>=30%<=35%	143-22-6	Toxic	Rat LD50=5300mg/kg
monobuhyl ether				LD50=6.6g/kg
				Rabbit:LD50mg/kg LD50µ/kg
Triethylene glycol	0-10%	112-27-6	WHMIS, not hazardous.	Rabbit: 16ml/kg 24H occluded
				rabbit. Rat16ml/kg , **see
				notes below**
*Diethylene glycol	5-10%	112-34-5	Toxic	Rat:LD50=5660mg/kg
monobuhyl ether				LD50=6.6g/kg Rabbit
	0-3%	6881-94-3	WHMIS, not hazardous.	LD 50mg/kg, LD 50g/kg
Diethylene glycol				LD 50 not available.
monopropyl ether				
Poly (ethylene oxide)	5-30%	25322-68-3	WHMIS, not hazardous.	LD 50 not available.
Diethylene glycol	0-5%	111-46-6	WHMIS, not hazardous.	Rat LD 50 =12565mg/kg
				Rabbit: LD 50=11890mg/kg

05-063

05-065

05-064 R529...

CROVER S

	IAIM I ELIME 24	AFELL DATA SHEET		03-000
Polyethelyne glycol	0-25%	9004-74-4	WHMIS, not hazardous.	l 05506 7t available.
monornethyl ether				
Polyethelene glycol	10-25%	9004-77-7	Toxic	LD 50 not available.
monobuhyl ether				
Triethylene glycol	0-50%	112-50-5	WHMIS, not hazardous	Rat: LD50=7750mg/kg
monornethyl ether				Rabbit: LD50m/kg.

^{*}Indicates toxic chemicals subject to the reporting requirements of Section 313 of title III and of 40 CFR are present.

Notes

Triethylene glycol: Rat male, Mortality: 0/5 Major Signs: Sluggishness, Unsteady Gail, Gross Pathology: None Rat Female, Mortality: 0/5 Major Signs: Sluggishness, Unsteady Gail, Gross Pathology: None

Rabbit: male, Mortality: 0/5 Major Signs: Emaciation and abdominal distension, Gross Pathology: Lungs discolored, stomach & intestines Liquid filled, slight visualization of skin at application site.

Rabbit: female, Mortality: 1/5 Major Signs: Emaciation and abdominal distension, Gross Pathology: Lungs discolored, stomach & intestines Liquid filled, slight visualization of skin at application site.

Significant Data with possible relevance to humans.

Evidence of kidney and liver injury was observed in rats receiving triethylene glycol, monomethyl ether at concentrations of 0.5% and grater in drinking water for 30 days. In studies in rates trithylene glycol monomethyl ether produced testicular atrophy when administered in drinking water over a 90 day period at dosage level of 4 g/kg day. This effects was not seen are oral dosage levels of 1.2g/kg /day or when applied to the skin for 90 days at the highest dosage levels.attainable.4g/kg/day Evidence of developmental toxicity in the presence of maternal toxicity was noted in offspring of pregnant receiving large oral doses of triethlene glycol monomethyl ether. Doses of 1250 mg/kg/day and higher administered during the period of organogenesis were associated with effects typically attributed to delayed development. A dose of 1000mg /kg was a clear. No observed effects level (NOEL) for developmental toxicity in this species. No evidence of developmental toxicity was noted in rabbits even at doses as high as 1500mg/kg a dose which was severe to the mothers contains one or more amines, which may react with nitrites to form Nitrosomonas. Some nitrosomonas have been shown to be carcinogenic in laboratory animals.

Triethylene glycol was given to rats by inclusion in their diet for 90 days at all concentrations of 10000, 20000, or 50000ppm. At the highest dose there were decreases in body weight. Physiologic response to these high doses was observed in kidney weights and urinalysis. No specific organ toxicity was seen.

In a 9-day (whole body) repeated inhalation exposure (6hr/day) study with rats, mortality occurred at 4284mg/me and effects included eye irritation and increases alanine aminotransferase and alkaline phosphates activities.: at 494 mg/me there were slightly increased alkaline phosphates activity. In a subsequent 9-day (nose only) repeated aerosol study rats were exposed to concentrations up to 1036 mg/me. The only effect noted was slight (not statistically or biologically significant) decreased in body weight gain at 517mg/m³ and a 1036 mg/m³ but not at 102mg/me. No indications of local or systemic target organ toxicity were noted including effects on hematology, clinical chemistry or urinalysis. In a sensory irritation study in mice, exposure to high concentrations of triethylene glycol aerosol resulted in a decreased respiratory rate. The RD50 or the concentration which produced a 50% decrease in respiratory rate was 5.1 mg/l There was no evidence in developmental toxicity studies for either embryo toxic or Teretogenicity effects in mice or rats given triethylene glycol by gavages. Maternal toxicity was seen as reduced body weight and food consumption increased water consumption and increased relative kidney weight with rats and clinical signs and increased relative kidney weight with mice. There was no histologic evidence of damages to the kidneys in either species. The no -observed effects doses for maternity toxicity were 1125 mg/kg/day for rats and 5630 mg/kg/day for mice. Minor fetotoxicity (reduced fatal body weights and increased skeletal variations) was present with doses of 11260 mg/kg/day for rats and 5630 and11260mg/kg/day for mice. The no observable effect dose for fetotoxicity was 5630 mg/kg/day for rats and 563mg/kg/day for mice. A chronic dietary feeding study of diethylene glycol with rats showed mild kidney injury at 1% while concentrations of 2% and 4% caused more marked kidney injury. In addition at 2% and 4% of diethylene glycol in the diet some rats developed benign papillary tumors in the urinary bladder. These have been attributed to the presence of urinary bladder calcium oxalate stones. No evidence for carcinogenicity was found with a chronic skin painting study with

REV Brake Fluid Dot3

05-063 05-064

05-065 05-066 R529...



MATERIAL SAFETY DATA SHEET

dethylene glycol in mice. The absence of a direct chemical carcinogenic effect accords with the results in in direct of a direct chemical carcinogenic effect accords with the results in in direct chemical carcinogenic effects. A feeding study employing up to 5.0% diethylene glycol in the diet failed to produce any teratogenic effects. In a mouse continuous breeding study with large doses of diethylene glycol in drinking water there was no evidence for reproductive toxicity at 3.5% (equivalent to 6.1 mg/kg/day) as reduced numbers of litters live pups per litter and live pup weight. No such effects were seen at 1.75% (approximately 3.05 g/kg/day). The relevance of these high dosages to human health is uncertain. Pregnant rats receiving undiluted diethylene glycol by gavage over the period of organogenesis has toxic effects at 410 and 8.0ml/kg/day as mortality decreased body weight decreased food consumption and increased liver and kidney weights. Fetotoxicity was seen only at these maternally toxic dosages. Decreased fatal body weight occurred at 8.0ml/kg/day and increased sketetal variants at 4.0 and 8.0ml/kg/day. No embryo toxic or teratogenic effects were seen neither maternal toxicity nor fetotoxicity occurred at 1.0 ml/kg/day. In a study with mice also receiving undiluted diethylene glycol over the period of organogenesis maternal toxicity occurred at 2.5 and 10.0 ml/kg/day but not at 0.5ml/kg/day Definitive developmental toxicity was seen in this species. An acute nose —only exposure (4-hr) to an irrespirable aerosol (2.83-2.53 microns) of diethylene glycol at amean concentration of 5.08mg/l produced no sins of toxicity or irritancy.

SECTION 111 - PHYSICAL /CHEI	IICAL CHARACTERISTICS
Boiling Point: 260°C	Specific Gravity: (H20=1): 1.039
Vapour Density: Heavier than air	Evaporate rate: Slower than ether
Coating V.O.C: N/A	Solubility in water: Soluble
Material V.O.C N/A	Appearance and odour: transparent yellow liquid with a mild odour.

Section 1V –FIRE A	ND EXPLOSION F	IAZARD O	F MATERIA	AL					
Flash Point(COC):	230°C								
Flammable Limits in air	by volume : Lower:	N/A	Upper:	N/A					
Extinguishing Media: I	oam, Alcohol foam,	Co₂, Dry che	mical and wa	iter fog.					
Special Fire Fighting Pro similarly approved self- or foam into hot burning	contained breathing	apparatus. (Cool fire expo	osed conta	ainers with	-	-	_	
Unusual fire and explos	ion hazards: Treat a	s petroleum	oil type prod	duct. Toxi	ic combus	tion by-pr	oducts ma	y be genera	ated.

SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to avoid: Avoid excessive temperatures. Warning: do not mix this product with either nitrites or nitro sating agents, because a nitrosamine may be foamed. Nitrosamines may cause cancer.

Incompatibility (Materials to avoid): Strong alkalizes high temperatures in the presence of strong bases, acids or strong oxidizing agents.

Hazardous decomposition or by-products: Incomplete combustion can produce carbon monoxide, carbon dioxide, unidentified hydrocarbons and other harmful product.

05-063

R529... 05-064



MATERIAL SAFETY DATA SHEET

Polymerization: Will not occur.

05-066 05-067

05-065

SECTIONVI (a) - HEALTH HAZARD DATA

Inhalation health risking and symptoms of exposure: Inhalation of mists and vapors may cause pulmonary irritation, dizziness and nausea and in severe cases the victim may be overcome by the mist or vapor.

Skin and eye contact health risks and symptoms of exposure: Product is not expected to be a primary skin irritant. Repeated skin contact may cause defecting of the skin and subsequent irritation. Eye contact may cause irritation.

Skin absorption health risks and symptoms of exposure: product is not expected to be absorbed through the skin.

Ingestion health risks and symptoms of exposure: Ingestion may cause gastrointestinal irritation, nausea and vomiting.

SECTIONVI (b) - HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute Inhalation: Exposure to high concentrations of aerosol generated at room temperature may cause lung injury and liver dysfunction. Skin contact- repeated or prolonged exposure may cause discomfort and local redness, defecting and drying of the skin. Eye contact- Irritation. Ingestion- Gastrointestinal irritation, nausea and vomiting. Components of this formulation have caused slight embryo fetal toxicity (delayed development), but no increase in birth defects in laboratory animals.

CARCINOGENICITY:

IARC MONOGRAPHS?

OSHA REGULATED?

See Section II above.

Medical Conditions Generally aggravated by exposure: Sensitivity of skin to oils and other petroleum products.

Emergency and First Aid Procedures: Inhalation Overexposure: Move victim to fresh air, administer artificial respiration. If necessary and seek medical aid. Skin contact: Wash with soap and water. Eye contact: Flush eyes with water for 15 minutes, holding eyelids open. If irritation persists, contact a physician. Ingestion: if patient is fully conscious give 2 glasses of water. Induce vomiting. If spontaneous vomiting occurs, keep head below hips to reduce chance of aspiration into lungs. Consult physician immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled: Small spills can be flushed with large amounts of water. For large spills. Transfer the bulk material into another container. Contained spilled material with dike a boom. Absorb material with suitable absorbent. Pick-up absorbed material in accordance with local, provincial and federal regulations.

Waste disposal method: Employ normal procedures for petroleum products with consideration for the chemical contents of the product. Dispose in accordance with local provincial and federal regulations.

Precautions to be taken in handling and storing: Petroleum product. Keep clean and dry. Do not store near sources of ignition. Do not leave partial drums or containers open? Keep out of children.

Other precautions. Empty drums retain hazardous product residue. All precautions must be followed when empty. Do not use or store empty drums near heat open flame or welding torches.

SECTION VIII - CONTROL MEASURES

Respiratory Protection: Not normally required. In enclosed areas, chemical respirators and /or self contained breathing apparatus may be necessary.

Ventilation: Mechanical ventilation is not normally required.

Protective Gloves. Chemical resistant gloves are recommended.

Eye Protection: Splash proof safety gloves are recommended.

Other Protective Clothing or Equipment: Protective aprons may be desirable.

Work/Hygienic Practices: Basic personal hygienic practices such as washing before eating are advised.

REV Brake Fluid Dot3

05-063 05-064

05-065

05-066 05-067 R529...

THIS MSDS WAS PREPARED ON January 15, 2017

SECTION IX – PREPARATION DATE OF M.S.D.S.

DISCLAIMER OF WARRANTY: The information contained herein is based upon data available to us and reflects our best professional judgment. However no warranty of merchantability fitness for any use or any other warranty is expressed or implied regarding the accuracy of such data. The results to be obtained from the use thereof or that any such use do not infringe any patent. Since the information contained herein may be applied to under conditions of use beyond our control and with which we may be unfamiliar, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATIONS. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose and circumstances.

MATERIAL SAFETY DATA SHEET