K-G PACKAGING 8001 KEELE STREET, P.O BOX 89 CONCORD; L4K 1Y8; ONTARIO CANADA 905--669-9855

Red Stallion Part# 05-412

PRODUCT: 11111-M107 METALLIC SILVER







Section 01: CHEMICAL PRODUCT AND CO	OMPANY IDENTIFICATION
-------------------------------------	-----------------------

MANUFACTURER K-G PACKAGING INC. 8001 KEELE STREET P.O. BOX 89 **ONTARIO** CANADA L4K 1Y8 CANUTEC EMERGENCY #:1-613-996-6666(24HR) 11111-M107 METALLIC SILVER PRODUCT NAME.

PRODUCT USES COATING

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route, Species	LC/50 Route, Species
CYCLOHEXANE	25-50	300 ppm	110-82-7	NOT AVAILABLE	NOT AVAILABLE
TOLUENE	15 - 30	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
ALUMINUM	1- 5	10 mg/m3 ACGIH	7429-90-5	NOT AVAILABLE	NOT AVAILABLE
ISOBUTANE	7-13	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY: ASPHYXIANT.
MAY CAUSE IRRITATION.

Section 04: FIRST AID MEASURES

IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION. EMERGENCY FIRST AID PROCEDURE

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... 287 - 480 WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A SPECIAL PROCEDURES..... (% BY VOLUME)

INCOMPLETE. AEROSOL FLAME PROJECTION

CLASSIFIED AS:..... >15cm BUT <100cm.

00007981	MATERIAL SAFETY DATA SHEET	Page 2						
PRODUCT: 11111-M107 METALLIC S								
Section	on 05: FIRE FIGHTING MEASURES	Red Stallion Part# 05-412						
FLASHBACKFLASH POINT(°C),TAG CLOSED-CUP(CONCENTRATE)	NONE. THE LOWEST KNOWN VALUE IS CYCLOHAXANE @ -:	20C.						
Section 06: ACCIDENTAL RELEASE MEASURES								
LEAK/SPILL	REMOVE ALL SOURCES OF IGNITION. USE AN INERT NON-SPARKING TOOLS, VENTILATE AREA, PREVENT	T ABSORBENT MATERIAL, AND T FROM ENTERING A WATERCOURSE.						
Section 07: HANDLING AND STORAGE								
STORAGE NEEDS ENGINEERING CONTROLS HANDLING PROCEDURES AND EQUIPMENT SYNERGISTIC MATERIALS	KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAM . VENTILATION - LOCAL (MECHANICAL IF USED INDOC STORE IN A COOL, WELL VENTILATED AREA NOT TO NONE KNOWN.	IES. DRS ON A CONTINUOUS BASIS). D EXCEED 50 DEG C.						
Section 08: EXP	POSURE CONTROLS/PERSONAL PROTECTION	DN						
GLOVES/ TYPERESPIRATORY/TYPEEYE/TYPEFOOTWEAR/TYPEOTHER/TYPE	(NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMME SAFETY GLASSES.	F A CARTRIDGE TYPE RESPIRATOR NDED.						
	PHYSICAL AND CHEMICAL PROPERTIES							
PHYSICAL STATE APPEARANCE. ODOR ODOR THRESHOLD VAPOUR PRESSURE(PSIG)-AEROSOL @ 20 C BOILING POINT (°C)(CONC) EVAPORATION RATE n-BUTYL ACETATE = 1 VAPOUR DENSITY (AIR=1) (BY WEIGHT) SOLUBILITY IN WATER g/L (20°C) pH SPECIFIC GRAVITY (LIQUID) COEFFICIENT OF WATERIOIL DIST FREEZING POINT: (°C) SPECIFIC GRAVITY (AEROSOL)	ALUMINIUM. SOLVENT ODOR. NOT AVAILABLE. 55-65. 80-111. GREATER THAN 1. GREATER THAN 1. NEGLIGIBLE. NOT APPLICABLE. 0.83-0.87. NOT AVAILABLE.							
	10: STABILITY AND REACTIVITY							
HAZARDOUS PRODUCTS OF	TO OTABLETT AND REACTIVITY							
CHEMICAL STABILITY:	HYDROCARBON FUMES AND SMOKE, CARBON MONO INCOMPLETE. UNDER NORMAL CONDITIONS	OXIDE WHERE COMBUSTION IS						
COMPATIBILITY WITH OTHER SUBSTANCES: NO, WHICH ONES? REACTIVITY CONDITIONS?	STRONG OXIDIZING AGENTS.							
HAZARDOUS POLYMERIZATION								
IRRITANCY OF MATERIALSENSITIZING CAPABILITY OF MATERIALCARCINOGENICITY OF MATERIALTERATOGENICITYMUTAGENICITY	LINICALONAL	ERATOCIANO EFFECTO ARE						
Section 12: ECOLOGICAL CONSIDERATIONS								
ENVIRONMENTAL	NOT AVAILABLE.							

00007981	Page 3						
PRODUCT: 11111-M107 METALLIC SI	LVER						
Section	Red Stallion Part# 05-412						
WASTE DISPOSAL	DISPOSALDO NOT PUNCTURE OR INCINERATE CONTAINERS, ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDE						
Section 1	4: TRANSPORTATION INFORMATION						
T.D.G. CLASSIFICATION D.O.T. CLASSIFICATION	CONCINED COMMODITATION						
Section 15: REGULATORY INFORMATION							
CANADIAN REGULATIONS:							
WHMIS CLASSIFICATION CNFC SECTION 3.3.5 CEPA (Canadian Environmental Protection Act)	A,B5,D2A,D2B. LEVEL 3. ALL SUBSTANCES IN THIS PRODUCT ARE LISTE SUBSTANCES LIST (DSL) OR ARE NOT REQUIRE	ED ON THE CANADIAN DOMESTIC					
U.S. REGULATIONS:		LO TO BE LISTED.					
HMIS RATING HEALTH	4 SEVERE HAZARD. 1 SLIGHT HAZARD. B. LEVEL 3. THIS PRODUCT CONTAINS THE FOLLOWING SU REQUIREMENTS OF SECTION 313 OF TITLE III O REAUTHORIZATION ACT OF 1986 AND 40 CFR P. CAS #: CHEMICAL NAME: *108-88-3 TOLUENE .*108-89-5 ALUMINUM, POWDERE CYCLOHEXANE. *110-82-7 CYCLOHEXANE. THE FOLLOWING STATEMENT IS MADE IN ORDER	ED TO COMPLY MUTILITIES ON ITERATION					
TSCA (Toxic Substances Control Act)	WARNING: THIS PRODUCT CONTAINS A CHEMIC TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCT CAS #: CHEMICAL NAME: *108-88-3 TOLUENE. ALL COMPONENT OF THIS PRODUCT ARE LISTE	CAL KNOWN TO THE STATE OF CALIFORNIA UCTIVE HARM.					
COMPLIES WITH CARB MIR =1.90 FOR METALLIC COATINGS.							
Section 16: OTHER INFORMATION							
	THE INFORMATION ON THIS MATERIAL SAFETY PACKAGING INC. FREE OF CHARGE, WHILE BELL USE BY SKILLED PERSONS AT THEIR OWN RISK RESPONSIBILITY FOR EVENTS RESULTING OR DINFORMATION ON THIS MATERIAL SAFETY DATA MATERIAL DESIGNATED HEREIN AND DOES NOT ANY OTHER MATERIAL OR IN ANY PROCESS. TECHNICAL SERVICES Jan14/11	EVED TO BE RELIABLE, IT IS INTENDED FOR K-G PACKAGING INC. ASSUMES NO PAMAGES INCURRED FROM ITS USE. THE					