SAFETY DATA SHEET

1. Identification

Product Identifier 14-254 SCENTED BRAKE CLNR 390G

Other means of Identification

Product code 1000022387 Recommended use cleaner **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company name RED STALLION INC. **Address** 395 PASSMORE AVE. TORONTO, ON M1V 4B3

Canada

Telephone **General Assistance**

Website www.redstallion.ca E-mail john@redstallion.ca

Emergency phone number Emergency - US

1-866-836-8855 **Emergency - Outside US** 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2 **Health hazards** Skin corrosion/irritation Category 2 Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

1-416-321-9980

Specific target organ toxicity, repeated

exposure

Category 2

Aspiration hazard

Category 1

Label elements



Signal word Danger

Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause Hazard statement

drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging

fertility. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep Response

comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Product name: 14-254 SCENTED BRAKE CLNR 390G

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards

Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

Category 2

long-term hazard

Other hazards

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

delayed

Chemical name	Common name and synonyms	CAS number	<u>%</u>
n-Hexane		110-54-3	54.358
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	33.521
Ethyl Alcohol		64-17-5	4.95
Carbon Dioxide		124-38-9	4.4
Cyclohexane		110-82-7	2.718
Other components below reportable	levels		0.05341

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. symptoms/effects, acute and Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

medical attention and special Symptoms may be delayed treatment needed

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

media

Specific hazards arising from the chemicalContents under pressure. Pressurized container may explode when exposed to heat or flame.
During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefightersFirefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

Product name: 14-254 SCENTED BRAKE CLNR 390G
Product #: 1000022387 Version #: 01 Issue date: 04-08-2016

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
Canada, Alberta OELs (Occupation	al Health & Safety Code, Sc	nedule 1, Table 2)	
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	344 mg/m3	
,		100 ppm	
Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3	
		1000 ppm	

Product name: 14-254 SCENTED BRAKE CLNR 390G

Product #: 1000022387 Version #: 01 | Issue date: 04-08-2016 3 / 10

n-Hexane (CAS 110-54-3)	TWA		17	'6 mg/m3
TENOXATIO (O/10 T TO-0-1-0)	1007) ppm
Canada. British Columbla OELs. (Occ Safety Regulation 296/97, as amende		xposure Limits fo	or Chemical Su	ıbstances, Occupational Health and
Components	Туре		Va	alue
Carbon Dioxide (CAS 124-38-9)	STEL	·	15	6000 ppm
	TWA		50	000 ppm
Cyclohexane (CAS 110-82-7)	TWA			00 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL			000 ppm
n-Hexane (CAS 110-54-3)	TWA		20	ppm
Canada. Manitoba OELs (Reg. 217/20		rkplace Safety An		alue
Components	Туре			
Carbon Dioxide (CAS 124-38-9)	STEL			0000 ppm
0 -	TWA			000 ppm
Cyclohexane (CAS 110-82-7)	TWA			00 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL			000 ppm
n-Hexane (CAS 110-54-3)	TWA) ppm
Canada. Ontario OELs. (Control of Ex Components	cposure to E Type	Biological or Cher		alue
Carbon Dioxide (CAS 124-38-9)	STEL		30	0000 ppm
	TWA		50	000 ppm
Cyclohexane (CAS 110-82-7)	TWA			00 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL			000 ppm
n-Hexane (CAS 110-54-3)	TWA) ppm
Canada. Quebec OELs. (Ministry of L Components	abor - Regu. Type	lation Respecting	-	f the Work Environment) alue
Carbon Dioxide (CAS 124-38-9)	STEL		54	1000 mg/m3
,			30	0000 ppm
	TWA			000 mg/m3
				000 ppm
Cyclohexane (CAS 110-82-7)	TWA)30 mg/m3
				00 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA			380 mg/m3
- H (040 440 F4 0)	T3.040			000 ppm
n-Hexane (CAS 110-54-3)	TWA			'6 mg/m3) ppm
ogical limit values				
ACGIH Biological Exposure Indices				
Components Value		Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3) 0.4 mg/l	,, .	2,5-Hexanedio n, without hydrolysis	Urine	*

Canada - Alberta OELs: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Product name: 14-254 SCENTED BRAKE CLNR 390G Product #: 1000022387 Version #: 01 Issue date: 04-08-2016 Canada - British Columbia OELs: Skin designation

Can be absorbed through the skin. n-Hexane (CAS 110-54-3)

Canada - Manitoba OELs: Skin designation

n-Hexane (CAS 110-54-3)

Canada - Ontario OELs: Skin designation

Can be absorbed through the skin. n-Hexane (CAS 110-54-3)

Canada - Quebec OELs: Skin designation

Can be absorbed through the skin. n-Hexane (CAS 110-54-3)

Canada - Saskatchewan OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Can be absorbed through the skin. n-Hexane (CAS 110-54-3)

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Can be absorbed through the skin.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove **Hand protection**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Gas **Physical state** Aerosol **Form**

Not available. Color Not available. Odor **Odor threshold** Not available.

Not available. рΗ Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

1.7 °F (-16.8 °C) estimated Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

1.4 % estimated Flammability limit - lower

(%)

Flammability limit - upper

7.3 % estimated

Not available. Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available. Vapor pressure

Not available. Vapor density

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

450.74 °F (232.64 °C) estimated

Decomposition temperature

Not available. Not available.

Other information

Not explosive. **Explosive properties** Not oxidizing. **Oxidizing properties** Specific gravity 0.483 estimated

10. Stability and reactivity

Reactivity

Viscosity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Incompatible materials **Hazardous decomposition** Strong oxidizing agents.

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact

Causes skin irritation.

Eye contact Ingestion

Causes serious eye irritation.

Symptoms related to the

Expected to be a low ingestion hazard.

physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

> 60000 ppm

cause redness and pain.

Information on toxicological effects

Acute toxicity

Narcotic effects.

Mouse

Acute toxicity	Talloons chooks.	
Components	Species	Test Results
Cyclohexane (CAS 110-82-	-7)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32880 mg/m3, 4 Hours
		> 5540 ppm, 4 Hours
Oral		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 5000 mg/kg
Ethyl Alcohol (CAS 64-17-5	5)	
<u>Acute</u>		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours

Product name: 14-254 SCENTED BRAKE CLNR 390G

Components	Species	Test Results
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
		7800 ml/kg
Naphtha, (Petroleum), Hydro	treated Light (CAS 64742-49-0)	
Acute		
Dermal		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
n-Hexane (CAS 110-54-3)		
<u>Acute</u>		
Dermal	D 11.4	> 2000 mg/kg 4 Hours
LD50	Rabbit	> 2000 mg/kg, 4 Hours
		> 5 ml/kg, 4 Hours
Inhalation	D-4	> 5000 ppm, 24 Hours
LC50	Rat	> 31.86 mg/l
		<u>-</u>
		73860 ppm, 4 Hours
Oral	Pot.	24 ml/kg
LD50	Rat	24 ming 24 g/kg
	Mediana	
	Wistar rat	49 g/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

•

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity May cause cancer.

Canada - Manitoba OELs: carcinogenicity

ETHANOL (CAS 64-17-5)

Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity

Suspected of damaging fertility.

Product name: 14-254 SCENTED BRAKE CLNR 390G
Product #: 1000022387 Version #: 01 Issue date: 04-08-2016

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure. Central nervous system. Respiratory system, Eves. Skin, Peripheral nervous system.

Aspiration hazard

Not likely, due to the form of the product.

Chronic effects

Causes damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Cyclohexane (CAS 11	0-82-7)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
Ethyl Alcohol (CAS 64	l-17-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours
n-Hexane (CAS 110-5	i4-3)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cyclohexane 3.44 **Ethyl Alcohol** -0.31n-Hexane 3.9

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name Transport hazard class(es) AEROSOLS, flammable

Class

2.1 Subsidiary risk

Packing group Not applicable.

Environmental hazards

Product name: 14-254 SCENTED BRAKE CLNR 390G

Special precautions for user Not available.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity.

IATA

UN number UN1950

UN proper shipping name Aer

Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards Yes ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only

Allowed with restrictions.

Not applicable.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes imS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG; TDG



Marine pollutant



15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

On inventory (yes/no)*

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Carbon Dioxide (CAS 124-38-9)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Carbon Dioxide (CAS 124-38-9)

Inventory name

Listed.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 04-08-2016

Version # 01

United States & Puerto Rico

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product name: 14-254 SCENTED BRAKE CLNR 390G
Product #: 1000022387 Version #: 01 Issue date: 04-08-2016

Yes